



Off-Body Performance in a WBAN over an Underground Mine

Authors

Moulay El Azhari

Underground Communications Research Laboratory, UQAT

moulay.el-azhari@uqat.ca
Val-d'Or, J9P 1Y3, Canada

Mourad Nedil

Underground Communications Research Laboratory, UQAT

mourad.nedil@uqat.ca
Val-d'Or, J9P 1Y3, Canada

Yassine Salih-Alj

School of Science and Engineering, Al Akhawayn University in Ifrane

y.alj@aui.ma
Ifrane, 53000, Morocco

Larbi Talbi

Department of Computer Science and Engineering, UQO

larbi.talbi@uqo.ca
Gatineau, J8X 3X7, Canada

Ismail Ben Mabrouk

Department of Computer Science and Engineering, UQO

ismail.benmabrouk@gmail.com
Gatineau, J8X 3X7, Canada

Khalida Ghanem

Division Architecture des Systèmes, CDTA

kghanem@cdta.dz
Algiers, 16081, Algeria

Abstract

The impact of a peculiar confined environment (i.e., underground mine) on the characteristics of the WBAN (Wireless Body Area Network) channel is evaluated in this article. Channel characteristics of WBAN are different from those of other wireless channels, especially in the presence of shadowing obstacles at Non-Line-of-Sight (NLOS). Moreover, directive antennas could be used for off-body communications as a mean to minimize the interaction with human body. Hence, in this study, the off-body performance of a single-input single-output (SISO) system was evaluated in Non-Line-of-Sight (NLOS) situations and compared with Line of Sight (LOS) measurements, at the 2.45 GHz band, for two antenna setups. Experimental results of the Rician k -factor, RMS delay spread, and path loss are obtained and discussed from measurements conducted at an underground mine gallery with Patch and Omnidirectional antennas. The results show that the average value of the Rician k -factor generally increases with distance, due to an increased multipath energy losses compared to the LOS energy loss. Moreover, the path loss exponent decreases at NLOS while the path loss values are increased due to human shadowing obstacle. The channel capacity is decreased at NLOS and as we increase the distance, due to the path loss effect. Directivity did not have a significant impact on the channel parameters.

Key Words

Channel capacity, Off-body channel, SISO, WBAN.

I. INTRODUCTION

Recent advances in wireless technology have led to the development of wireless body area networks (WBAN). WBAN is a conceptual wireless network technology where a set of communicating devices are located in a distributed sensor network around the human body [1]. Data of vital body parameters and movements is collected and communicated using short-range wireless communication techniques to a close by command station. Wireless Off-body communication is a technology that deals with the communication links between devices mounted on the body, and other devices, or access points, away from the body. It found applications in the industrial, entertainment, sport, and medical fields. Among the examples of this technology are wearable RFID tags and medically oriented body-worn sensors. In off-body links, much precision and attention should be taken in antenna design, placement, and orientation. For optimal off-body communication, the antennas' radiation patterns should be directed away from the body [2].

Recently, the rising accidents rates in the mining field pushed toward exploring new communication schemes destined to the safety of the miners in such off-body communication scheme. Indeed, the off-body technology has emerged as a promising communication scheme dedicated to the miners' safety [3-4]. Toxic gases' levels could be displayed to the miners and vital information could be delivered to the command station, in a timely manner. This allows improving the miners' safety and health through the fast detection of potential problems which eases the decision making. However, in a mine environment, the reliability of the wireless link is affected by short-term and long-term fading mainly caused by multipath communication, and shadowing [1]. Moreover, the off-body communication link performance depends on the allocated frequency band and the directivity of the transmitter (Tx) and the receiver (Rx) antennas. Hence, a good characterizing study of the off-body channel in a mine environment should explore the effect of directivity and link obstruction at NLOS.

This work focuses on the 2.45 GHz ISM (industrial, scientific and medical) band. This band is suitable for off-body propagation studies [5]. At this frequency, the propagation is due to creeping waves and multipath signals resulting from the reflections at the surrounding environment [6]. Numerous papers in the literature deal with off-body communication systems, for patients' vital signs monitoring application as well as entertainment applications [1-2]. Moreover, the 2.45 GHz band has been thoroughly investigated for applications in a mine gallery, for regular radio transmission (not involving the human body), using different kinds of antennas such as monopole and patch antennas [7]. In fact, wireless communication systems in an underground environment should be designed to provide reliable services with high throughput [8], bearing in mind that the link capacities are limited by the transmission power and the bandwidth of the radio link [9-10].

In our previous research studies [3-4], the off-body performance was investigated using monopole and patch antennas and a single-antenna setup was considered to assess the path loss, RMS delay spread and channel capacity. However, Rician k-factor was not considered to determine the best distribution that would approximate the corresponding capacity [3-4]. In this paper, k-factor results are presented along with the corresponding test for the best cumulative distribution function (CDF) approximation. Furthermore, the overall results characterizing the off-body channel in terms of the considered Rician k-factor, channel impulse response, path-loss, RMS delay spread and coherence bandwidth, at the 2.45 GHz band, are compared using two-antenna setups exploring the effect of directivity. The link obstruction at NLOS is also discussed

and the channel capacity is calculated (assuming a fixed transmitted power) and compared to five usual distributions in order to determine the closest CDF approximation. To ease the reading, the notations in Table 1 were used throughout the paper.

The remainder of the paper is organized as follows. Sec. II describes the measurements setup used to characterize the underground off-body channel and to evaluate the corresponding channel capacity for a WBAN. Sec. III combines the results from the different measurement scenarios to determine and discuss the different channel parameters. Finally, Sec. IV discusses the conclusions and results derived from this study.

TABLE 1. NOMENCLATURES FOR THE DIFFERENT CONFIGURATIONS.

Configuration	Patch		Monopole	
Link	LOS	NLOS	LOS	NLOS
Nomenclature	LOS-P	NLOS-P	LOS-M	NLOS-M

II. MEASUREMENT PROCEDURE FOR OFF-BODY CHANNEL CHARACTERIZATION IN A WBAN

WBAN Channels are classified into four categories (C1~C4), as illustrated in Fig. 1 [5]. These channels are categorized by their device location. The in-body channel (C1) is related to the inside of the body; the C2 channel is related to the surface and inside of the body; the on-body channel (C3) is related to the surface of the body and the off-body channel (C4) is related to off-body communications where the maximum distance is 5 m [1].




FIGURE 1. ILLUSTRATION OF WBAN CHANNELS.



FIGURE 2. MEASUREMENT SETUP IN THE CONSIDERED UNDERGROUND GALLERY.

In this paper, the off-body channel is characterized at the 2.45 GHz band and the corresponding measurements are conducted in a peculiar indoor environment, i.e., an underground gold mine located in Val-d'Or, Quebec, Canada, and managed by the Mining and Mineral Sciences Laboratories-Canadian Center for Minerals and Energy Technology (MMSL-CANMET). The considered underground gallery is located at the 40 m underground level. It stretches over a length about 140 m with a width and height of about 3 m. Photography of the measurement setup in the corresponding underground gallery is shown in Fig. 2. The mine gallery consists mainly of very rough walls and uneven floor. Cables and pipes are stretched along these walls (near the ceiling). The temperature is maintained at 6 °C, with a humidity level of nearly 100 % throughout the year. There are some water puddles with different dimensions along the gallery and the water dripping through the walls.



FIGURE 3. MINING MACHINERY NEAR THE MEASUREMENT SETUP.




FIGURE 4. REPRESENTATION OF THE WBAN SYSTEM IN A MINE ENVIRONMENT.

There is mining machinery few meters away from the measurement' setup. Metal rods and screens cover the ceiling of the gallery contributing to multipath phenomenon within a dusty environment. The chosen site is an ideal environment to study the LOS and NLOS multipath propagation. The NLOS communication is achieved when the direct propagation path is obstructed by a human subject wearing miner's outfit, hence emulating the usual human shadowing activities inside the mine. Fig. 3 illustrates the mining machinery in a gallery near the measurement setup; Fig. 4 depicts a graphic representation of the WBAN system inside a mine.




FIGURE 5. ILLUSTRATION OF THE CONSIDERED MEASUREMENT SETUP.

TABLE 2. MEASUREMENT PARAMETERS.

Equipment	Parameter	Value
VNA (of type Anritsu)	Center frequency	2.45 GHz
	Number of points	6401
	Sweep time	Auto
	Calibration	Full-2-port
		(Tx power = -10 dBm)
Human body	Gender	Male
	Height	180 cm
	Weight	75 kg
Antenna	Type	Monopole
	Distance to body	5-10 mm
	Orientation	Head to Head

The process of calibration is necessary to remove the losses introduced by the cables from the measured frequency response S_{21} . Hence, the system calibration is performed at 1 m separation between the transmitter and the receiver. This 1 m Tx-Rx separation do is picked to be the reference distance for the path loss modeling. After the calibration, all the parameters were configured, namely the transmitted power, the frequency range, and the number of points as presented in Table 2.

The measurements campaign aims to investigate the small and the large scale variations in the fading signal. Large-scale channel characterization consists of path loss (PL) and shadowing effect, while the small-scale channel characterization consists of small scale fading which is caused by the multipath propagation. The transmitting antennas were placed at a fixed position in the middle of the mine pathway. The receiving antennas were placed on the right side of the chest of a 1.80 m, 75 kg male subject wearing a miner's outfit, as seen in Fig. 2. The transmitting and the receiving antenna elements are kept at the same distance from ground. During the measurements, 6 data snapshots were collected at each distance, from a distance of 1 m through 5 m away from the transmitter, as shown in Fig. 5. The transmitting and receiving antennas were connected to the two ports of the previously calibrated vector network analyzer (VNA). At each snapshot, the S_{21} values were recorded for 6401 frequency samples around the center frequency of 2.45 GHz, as indicated in Table 2. The noise floor for the measurements was considered at -90 dBm, which is considerably higher than the average power for Nyquist Noise, the noise floor for the VNA, and the observed noise floor from the measurements.

III. RESULTS AND DISCUSSION

A. Channel impulse response

The channel impulse response $h(t)$ is acquired using the Inverse Fourier Transform (IFT) of the average of six measured channel frequency responses (given by the scattering parameter S_{21}). It can be seen that the LOS signal generally carries the highest power among the multipath received signals, when the link is not obstructed. In general, the first arriving multipath signal is highest for the smallest distances and decreases as the Tx-Rx separation increases. Some exceptions to this general result were observed; for example, in NLOS-M, the first arriving multipath component for a Tx-Rx separation of 5 m is higher than that of a Tx-Rx separation of 4 m due to constructive multipath additions. It is also observed that the received signal' power at LOS is higher than the corresponding NLOS power level for both the monopole and the patch antennas. Figs. 6 and 7 represent the impulse responses for the monopole and the patch antenna setups at the 2 m and 4 m distances.




FIGURE 6. IMPULSE RESPONSES FOR TX-RX SEPARATIONS OF 2 M AND 4 M FOR A MONOPOLE ANTENNA.

B. Rician K-Factor

The Rician k-factor is an indicator of link quality [11], measured as the relative strength of the direct and scattered components of the received signal, as expressed in the following equation [12]:

$$K(\text{dB}) = 10 \log \left(\frac{\varepsilon[H]^2}{2\text{var}(H)} \right) \quad (1)$$

where ε denotes the mathematical expectation (average) and $\text{var}(\bullet)$ refers to the variance of the channel vector H . The k-factor was calculated for each distance between Tx and Rx. Fig. 8 shows the Rician k-factor versus Tx-Rx separation for the monopole antenna setup, and Table 3 shows the k-factor statistics for the monopole and patch antenna setups. The results show that the Rician k-factor generally increases for the first three distances, decreases for the 4 m distance, and increase again for the 5 m distance. This is due to the fact that the scattered components encounter additional reflections against the walls, the ceiling and the floor, as the distance is increased; the additional reflections correspond to additional losses of multipath energy due to the increased propagation distance. This decrease in the multipath power (relative to the LOS power) is mitigated at the 4 m distance, due to the specific geometry of the gallery. Moreover, it is observed that the Rician k-factor for the monopole setup is higher than that of the patch setup. In fact the monopole antenna has a much larger bandwidth than the patch antenna; hence, the impulse response of the off-body channel using the patch antenna is wider than that which uses the monopole antenna as illustrated in Figs. 6 and 7. This means that the powers of the multipath signal (relative to the LOS signal power) when using the patch antenna are higher than their monopole counterparts, which explains the K-factor results.




FIGURE 7. IMPULSE RESPONSES FOR TX-RX SEPARATIONS OF 2 M AND 4 M FOR A PATCH ANTENNA.

C. Path loss

The path loss is defined as the ratio of the transmitted power to the local average of the received power [7]. It was obtained from the path gains, by averaging over the frequency samples and the different snapshots; it is mathematically represented as follows:

$$PL(d(p)) = -20 \log_{10} \frac{1}{N_s N_f} \sum_{j=1}^{N_s} \sum_{n=1}^{N_f} |H_j^p(n)| \quad (2)$$

where $PL(d(p))$ is the path loss at the position of p (with Tx-Rx separation $d(p)$); N_s and N_f are the number of the snapshots and frequency samples, respectively. $H_j^p(n)$ denotes the measured S_{21} for the position p , j^{th} snapshot, and n^{th} frequency sample [2]. When expressed in terms of the Tx-Rx distance, the path loss is modeled as follows [7]:

$$PL(d) = PL_{dB}(d_0) + 10 \cdot \alpha \cdot \log_{10} \left(\frac{d}{d_0} \right) + X \quad (3)$$

where $PL_{dB}(d_0)$ is the mean path loss at the reference distance d_0 , d is the distance where the path loss is calculated, α is the path loss exponent (determined using least square linear regression analysis), and X is a zero mean Gaussian variable (in dB) [7].

The path loss results and a linear regression of these values are plotted in Figs. 9 and 10, for both the patch and monopole antennas at the LOS and NLOS situations.

TABLE 3. STATISTICS OF THE K-FACTOR FOR THE OFF-BODY CHANNELS INSIDE THE MINE GALLERY (MINIMUM, MAXIMUM, AVERAGE AND STANDARD DEVIATION MEASURED VALUES).

	Min	Max	Mean	Std
k-factor (dB) LOS-M	2.7356	5.9711	4.3024	1.3779
k-factor (dB) LOS-P	-2.4332	-1.2148	-1.9021	0.4762




FIGURE 8. K-FACTOR FOR THE LOS-M OFF-BODY CHANNELS.




FIGURE 9. PATH LOSS VALUES AND THEIR LINEAR REGRESSION FOR THE MONOPOLE ANTENNA.




FIGURE 10. PATH LOSS VALUES AND THEIR LINEAR REGRESSION FOR THE PATCH ANTENNA.

TABLE. 4. PL EXPONENT VALUES FOR THE DIFFERENT OFF-BODY CHANNEL CONFIGURATIONS.

Configuration	Patch		Monopole	
Parameters	LOS	N-LOS	LOS	N-LOS
PL-exponent	2.48	1.26	2.16	1.19

The path loss exponent α is found to be close to the free-space path-loss exponent (which is equal to 2) for the LOS configurations, for both the monopole and the patch antennas. Hence, the linear regression analysis suggests that the off-body signal decays in LOS with about the same rate as it would decay in free space. The results in Table 4 show that, relative to a LOS scenario, the path loss exponent decreases in NLOS configurations for both monopole and patch antennas.

However, the path loss values at NLOS are higher compared to a comparable LOS scenario due to the shadowing effect of the human obstacle. This suggests that the signal is damped slower in NLOS due to constructive multipath power additions. This result is expected because the path loss exponents are typically low for Off-body links in NLOS cases as discussed in [13-15].

D. Time dispersion parameters

The time dispersion parameters are determined from the power delay profile (PDP), which represents the power received in the time domain. PDP is determined by calculating the statistical average of the magnitude squared of the impulse response as follows:

$$\text{PDP}(t) = \langle |h(t)|^2 \rangle \quad (4)$$

The RMS delay spread and the coherence bandwidth, shown in Figs. 11 and 12, were determined using equations (5) and (6) respectively, as follow [16]:

$$\tau_{RMS} = \sqrt{\overline{\tau^2} - \bar{\tau}^2} \quad (5)$$

where $\bar{\tau}$ denotes the mean excess delay and $\overline{\tau^2}$ is the second moment of the PDP, while the coherence bandwidth is

$$B_c \approx \frac{1}{5\tau_{RMS}} \quad (6)$$

In general, the RMS delay spread increases whereas the coherence bandwidth decreases with the increase of the distance, for both the monopole and the patch antenna setups. One exception of this result happens in the distance of 5 m where the RMS delay spread values are smaller compared to the 4 m values for both the monopole and the patch antennas. This is due to the fact that the multipath richness is higher for the 4 m distance than the 5 m distance at NLOS. Fig. 12 shows RMS delay spread values that are between 15 ns and 66 ns and coherence bandwidths in the range of 3-14 MHz for the LOS-M case. For the NLOS-M conditions, the RMS delay spread is between 35 ns and 82 ns.

From Fig. 11, the patch antenna setup exhibits higher values of the RMS delay spread (lower values of the coherence bandwidth) compared to the corresponding monopole setup measurements. These results are due to the fact that the monopole antenna is able to collect a stronger LOS or creeping wave component (compared to the multipath components) than the patch antenna, due to its large bandwidth as explained by the k-factor results. Moreover, the RMS delay spread is smaller at LOS compared to NLOS due to the increased multipath richness and decreased power of the first multipath component (relative to the other multipath signals) at NLOS.




FIGURE 11. TIME DISPERSION VALUES VS. DISTANCE FOR THE PATCH SETUP.




FIGURE 12. TIME DISPERSION VALUES VS. DISTANCE FOR THE MONOPOLE SETUP.

E. Channel Capacity

Channel capacity CDFs are plotted in Figs. 13 and 14 for monopole and patch setups at LOS; Fig. 15 represents the average capacities for the monopole and patch setups at both LOS and NLOS situations. This channel capacity is derived from measurements using Shannon formula as follows [17]:

$$C_N \left[\frac{\text{bps}}{\text{Hz}} \right] = \log_2 \left(1 + \rho |H|^2 \right) \quad (7)$$

where H is the normalized channel response and ρ is the average signal to noise ratio (SNR).




FIGURE 13. CAPACITY CDFs FOR THE FIVE LOS-M OFF-BODY CHANNEL DISTANCES.




FIGURE 14. CAPACITY CDFs FOR THE FIVE LOS-P OFF-BODY CHANNEL DISTANCES.




FIGURE 15. AVERAGE CHANNEL CAPACITY VS. DISTANCE.




FIGURE 16. LOS-P CAPACITY CDF PLOT, WITH COMPARISON TO THE DIFFERENT CDF APPROXIMATIONS.




FIGURE 17. NLOS-P CAPACITY CDF PLOT, WITH COMPARISON TO THE DIFFERENT CDF APPROXIMATIONS.




FIGURE 18. LOS-M CAPACITY CDF PLOT, WITH COMPARISON TO THE DIFFERENT CDF APPROXIMATIONS.




FIGURE 19. LOS-M CAPACITY CDF PLOT, WITH COMPARISON TO THE DIFFERENT CDF APPROXIMATIONS.

The above results show that the channel capacity at a certain probability level decreases with distance at LOS. This is explained by the fact that the smaller distances correspond to higher received average powers and hence higher average SNRs which have a direct impact on the capacity as given in (3). Moreover, it is observed that capacity values in NLOS situations are smaller than their corresponding LOS values due to the decay in power associated with the human shadowing effect. Comparing the channel capacities for the monopole and the patch setups, it is observed that the NLOS-M capacities are higher than the corresponding NLOS-P capacities. Moreover, the LOS-M capacities at the 3 m and 5 m distances are higher than their corresponding LOS-P capacities. This is due to the ability of the monopole antenna, which has a broad bandwidth, to efficiently capture the LOS signal. Hence, the directivity of the patch antenna is only favorable at the smaller LOS distances, where the LOS component's power is considerably large due to the efficient Tx-Rx alignment.

The different configurations' capacity CDFs at the 3 m distance were compared to several CDF approximations as illustrated in Figs. 16-19. The most accurate approximations for both the LOS-P and LOS-M are the Rice and the Nakagami distributions. For the NLOS-P, the Rician and lognormal distributions best describe the capacity CDF of the measurements. Finally, for the NLOS-M, the Nakagami and Rician distribution best approximate the capacity CDF of the measurements. Furthermore, the Rayleigh distribution, which usually characterizes the radio channels' fading, does not characterize the patch nor monopole capacity distributions. This is due to the fact that the Rayleigh fading is not valid for WBAN distributions due to the presence of a strong direct link [10], which is established with LOS or creeping wave communications. In these conditions, the Rician distribution usually characterizes the WBAN channel, which explains the results.

IV. CONCLUSION

In this paper, the off-body channel was characterized at 2.45 GHz for a WBAN in a mine gallery using patch and monopole antennas considering LOS and NLOS situations. It can be noted that the k-factor is not as high as expected in a short range line-of-sight (LOS) communication. This may be due to the presence of the human body involving creeping wave signals that attenuate more rapidly compared to the free space propagation. It was also observed that the path-loss exponent decreases in NLOS situations compared to a corresponding LOS situation for both monopole and patch antenna setups, due to constructive multipath combining. The monopole antenna setup exhibit lower values of the RMS delay spread compared to their corresponding patch setup' RMS delay spread values. This is due to the fact that the monopole antenna (which has a large beam width) is able to collect the LOS or the creeping wave component better than the patch antenna. The RMS delay spread is higher at NLOS situations compared to a LOS situation for both antenna setups. This is due to the fact that the multipath powers increases (compared to the first arriving multipath signal' power) at NLOS. The Rician K-factor further emphasizes the time dispersion results (at LOS) with values generally increasing (except for the 4 m distance) due to the increased reflections through walls and ceiling. The channel capacities decrease with distance for both LOS-M and LOS-P, due to the path loss effect. At NLOS, the multipath richness did not overcome the shadowing of the LOS component, and hence the capacity is lower than that of a corresponding LOS situation. The NLOS-M capacities are higher than the corresponding NLOS-P capacities, because of the efficiency of the monopole antenna in capturing the LOS or the creeping wave signals. For both LOS and NLOS configurations, the Rician distribution approximates the CDF of the measurements (at the 3 m distance), due to the presence of either a strong LOS component or a strong creeping wave signal. Although both the patch and the monopole results are acceptable for underground communications, the channel parameters using the monopole setups are better than the corresponding patch setup parameters in most situations. The mine environment favors the use of the monopole antenna more than the patch antenna for off-body communications at the 2.45 GHz band. We conclude that an in-mine off-body system at 2.45 GHz destined to improve the security of the miners should use monopole antennas rather than the patch antennas.

REFERENCES

- [1] S.-H. Han and S. K. Park, "Performance Analysis of Wireless Body Area Network in Indoor Off-body Communication," in *IEEE Transactions on Consumer Electronics*, Vol. 57, No. 2, pp. 335-338, May 2011.
- [2] S.I.M. Sheikh, W. Abu-Al-Saud, and A. B. Numan, "Directive Stacked Patch Antenna for UWB Applications," *International Journal of Antennas and Propagation*, Vol. 2013, No. 389571, pp. 1-6, Nov. 2013.
- [3] M.E. El-Azhari, M. Nedil, Y. S. Alj, I. Benmabrouk, L. Talbi, and K. Ghanem, "Off-body LOS and NLOS channel characterization in a mine environment," in *Electrical and Information Technologies (ICEIT)*, 2015 International Conference on , vol., no., pp.114-118, 25-27 March 2015.
- [4] M.E. El-Azhari, M. Nedil, I. Benmabrouk, and L. Talbi, "Off-body channel characterization at 2.45 GHz in underground mine environment," *Proc. IEEE Antennas and Propagation Society Int. Symp. (APSURSI)*, pp.251-252, Jul. 6-11, 2014.
- [5] Opening Report for the TG6 session in Aug 2008, IEEE 802.15 P08-0576-00-0006.

- [6] I. Khan, P. S. Hall, A. A. Serra, A. R. Guraliuc, and P. Nepa, "Diversity Performance Analysis for On-Body Communication Channels at 2.45 GHz," *IEEE Trans. Antennas Propag.*, vol. 57, no. 4, pp. 956-963, Apr. 2009.
- [7] I. Ben Mabrouk, L. Talbi, M. Nedil and K. Hettak, "MIMO-UWB Channel Characterization Within an Underground Mine Gallery," *IEEE Transactions on Antennas and Propagation*, Vol. 60, No. 10, pp. 4866-4874, Oct. 2012.
- [8] Y. Salih-Alj, C. Despins and S. Affes, "Design considerations for an UWB computationally-efficient fast acquisition system for indoor line-of-sight ranging applications," *IEEE Transactions on Wireless Communications*, Vol. 10, No. 8, pp. 2776-2784, Aug. 2011.
- [9] P. Van Torre, L. Vallozzi, H. Rogier, M. Moeneclaey and J. Verhaevert, "Reliable MIMO communication between firefighters equipped with wearable antennas and a base station using space-time codes," *Proc. 5th European Conference on Antennas and Propagation (EUCAP)*, pp. 2690-2694, Apr. 2011.
- [10] I. Khan, P.S. Hall, A.A. Serra, A.R. Guraliuc and P. Nepa, "Diversity Performance Analysis for On-Body Communication Channels at 2.45 GHz," *IEEE Trans. Antennas Propagation*, Vol. 57, No. 4, pp. 956-963, Apr. 2009.
- [11] C. Tepedelenlioglu, A. Abdi, and G. Giannakis, "The ricean k factor: estimation and performance analysis," *Wireless Communications, IEEE Transactions on*, vol. 2, no. 4, pp. 799-810, 2003
- [12] Sarris, I. and A. R. Nix, "Ricean K-factor measurements in a home and an office environment in the 60 GHz band," *Mobile and Wireless Communications Summit*, 2007.
- [13] J. Hamie, "Contributions to Cooperative Localization Techniques within Mobile Wireless Body Area Networks," *PhD Manuscript, University of Nice-Sophia Antipolis*, Nov. 2013
- [14] R. Rosni and R. D'Errico, "Off-body channel modelling at 2.45 ghz for two different antennas", In *Antennas and Propagation (EUCAP), Proceedings of the 6th European Conference on*, pp 3378-3382, 2012.
- [15] B. Denis, N. Amiot, B. Uguen, A. Guizar, C. Goursaud, A. Ouni, and C. Chaudet, "Qualitative analysis of RSSI behavior in cooperative wireless body area networks for mobility detection and navigation applications," in *21st IEEE International Conference on Electronics Circuits and Systems (ICECS)* on , pp.834-837, 7-10 Dec. 2014.
- [16] T. S. Rappaport, "Mobile Radiop Propagation: Small scale Fading and Multipath," in *Wireless communications: principle and practice*, 2nd ed, Prentice Hall, 2001.
- [17] H. Inanoglu, "Multiple-Input Multiple-Output System Capacity: Antenna and Propagation Aspects," *IEEE Antennas and Propagation Magazine*, Vol. 55, No. 1, pp. 253-273, Feb. 2013.

AUTHORS' BIOGRAPHY

Moulay El Azhari received the Bachelor's degree in electrical and electronics engineering from California State University in Sacramento (CSUS), in 2005, the Master's degree in electrical and electronics engineering from California State University in Sacramento (CSUS) in 2008, and the Master's degree in telecommunications engineering from the University of Quebec in Abitibi-Témiscamingue, in 2013. He worked as an electrical engineer in motion control engineering R&D department from 2007 to 2011. He also served as a researcher at the Telebec Underground Communications Research Laboratory (LRTCS)

from 20013 to 2015, and he is currently pursuing his PHD studies at the University of Quebec in Outaouai (UQO). His research interests are in radio wave propagation for multiple-input and multiple-output systems, measurement campaigns in underground mine environments, and body area networks. Moulay El Azhari is a member of the Ordre des ingénieurs du Québec.

Mourad Nedil received the Dipl. Ing. degree from the University of Algiers (USTHB), Algiers, Algeria, in 1996, the D.E.A. (M.S.) degree from the University of Marne la Vallée, Marne la Vallée, France, in 2000, and the Ph.D. degree from the Institut National de la Recherche Scientifique (INRS-EMT), Université de Québec, Montréal, QC, Canada, in April 2006. He completed a postdoctoral fellowship at INRS-EMT, within the RF Communications Systems Group (2006–2008). In 2008, he joined the underground research laboratory (LRTCS), University of Quebec at Abitibi-Témiscamingue, QC, as an Assistant Professor. His research interests include antennas, MIMO radio-wave propagation, and microwave devices.

Yassine Salih-Alj received the Bachelor's degree in microelectronics from the University of Quebec at Montreal (UQAM), Montreal, Quebec, Canada, in 2001, and the Master's degree in electrical engineering from the École de Technologie Supérieure (ETS), Montreal, Quebec, Canada, in 2003, and the Ph.D. degree in Telecommunications from the National Institute of Scientific Research – Energy, Materials & Telecommunications (INRS-Telecom), Montreal, Quebec, Canada, in 2008. He served as a research assistant at the Telebec Underground Communications Research Laboratory (LRTCS) from 2005 to 2008, and then during 2009 as a Postdoctoral Fellow at Poly-Grames Research Center, of the École Polytechnique de Montréal, Montreal, Quebec, Canada. He is currently working as a permanent faculty member at the School of Science and Engineering (SSE) of Al Akhawayn University in Ifrane (AUI), Morocco. He has published over 40 publications and has been actively involved in IEEE events for the past five years, where he chaired and served as Technical Program Member or as distinguished reviewer for over 100 conferences. His research interests are in the areas of Wireless Communications, Indoor Positioning, UWB (Ultra-Wideband), Digital System Implementation, GPS (Global Positioning System) and Engineering Education.

Larbi Talbi received the M.S. and Ph.D. degrees in electrical engineering from Laval University, Quebec City, QC, Canada, in 1989 and 1994, respectively. He completed a postdoctoral Fellowship with the INRS-Telecommunications, Montreal, QC, within the Personal Communications Research Group (1994–1995), where he led projects supported by Bell-Canada. From 1995 to 1998, he was an Assistant Professor at the Electronics Engineering Department of Riyadh College of Technology, Saudi Arabia. During 1998–1999, he was an Invited Professor at the Electrical and Computer Engineering Department, Laval, University. Since 1999, he has been a Professor with the Department of Computer Science and Engineering, University of Quebec, Outaouais/Ottawa region, Canada, where he is the Ph.D. program Chair in Sciences and Information Technologies. His research activities include experimental characterization and modeling of UHF/EHF indoor radio propagation channels and the design of antennas and microwave circuits for wireless communication systems. Currently, he is actively involved in major projects related to the deployment of wireless technologies in Underground mines, mainly experimental characterization of the underground mine channels using MIMO antennas at 60 GHz, the design of microwave and RF components using SIW technique and metamaterials, and antenna array for wireless applications. He has authored or coauthored more than 170 journal and conference papers. Dr. Talbi is a member of the Ordre des ingénieurs du Québec

Ismail Ben Mabrouk was born in Hammam Lif, Tunisia, in 1984. He received the B.A.Sc. and M.A.Sc. degrees in electrical engineering from the University of Lille, Lille, France, in 2006 and 2007, respectively. He received the Ph.D. in information technology from the University Of Quebec, Outaouais/Ottawa region, Canada. His research activities have been centered on propagation studies for multiple-input and multiple-output systems, measurement campaigns in underground mine environments, and antenna design at millimeter wave.

Khalida Ghanem received the B.Sc. (Eng.) degree in electronics from the Ecole Nationale Polytechnique (ENP), Algeria, and the M.A.Sc. and Ph.D. degrees in telecommunications from INRS-EMT, University of

Quebec, Canada, in 2004 and 2008, respectively. From 1999 to 2000, she was with the Department of Mathematics, Electrical and Computer Engineering, University of Quebec at Rimouski (UQAR), Canada, where she worked as a Research Assistant on practical smart antenna systems. She then joined the University of Birmingham as a Research Associate at the School of Electronic, Electrical and Computer Engineering and the University of Southampton and Sheffield as a Research Visitor, in 2008 and 2009, respectively. From 2010 to 2011, she was an Assistant Professor with Prince Mohammad Bin Fahd University (PMU) in Kingdom of Saudi Arabia (KSA). Now she is a Main Researcher with CDTA, Center of Advanced Technologies, Algeria. Her research interests lie in the areas of wireless and mobile communications, and antennas and propagation. Dr. Ghanem is a recipient of various distinctions including the Quebec Governmental Postdoctoral Fellowship for Excellence in 2007. She was the Chair of the IEEE Women In Engineering Chapter in Montreal in 2007 and Vice Chair of the same society in KSA. She has also participated in the Technical Program and organizing committees for various conferences.